

Serial No. 09/252,485

Page 2 of 14

### **IN THE CLAIMS**

This listing of claims will replace all prior versions, and listings of claims in the application:

#### **Listing of Claims:**

Claims 1-41 (canceled).

Claim 42 (currently amended): An apparatus that outputs multiple video signals, comprising:

first signal processing components, wherein the first signal processing components process a first video signal, the first signal processing components comprising:

a first tuner;

a first demodulator coupled to the first tuner;

a first demultiplexor coupled to the first demodulator;

a first video/graphics/text demultiplexor coupled to the first demultiplexor,

wherein the first video/graphics/text demultiplexor separates graphics, video and text from the first video signal; and

a first video decompressor coupled to the first video/graphics/text demultiplexor; and

second signal processing components, wherein the second signal processing components process a second video signal, the second signal processing components also operable to scale and redirect the second video signal, the second signal processing components comprising:

a second tuner;

a second demodulator coupled to the second tuner;

a second demultiplexor coupled to the second demodulator;

a second video/graphics/text demultiplexor coupled to the second

demultiplexor, wherein the second video/graphics/text demultiplexor separates graphics, video and text from the second video signal; and

Serial No. 09/252,485

Page 3 of 14

a second video decompressor coupled to the second video/graphics/text demultiplexor, wherein the second signal processing components are located on an upgrade to card insertable into an existing set top terminal to provide digital picture-on-picture capability;

a third signal path having third signal processing components, wherein the third signal processing components process a third video signal, the third signal processing components also operable to scale and redirect the third video signal, wherein the third signal processing components are substantially identical to the first and the second signal processing components, and wherein the first, second and third video signals are displayed simultaneously on a display;

audio decompressors in the first, second and third signal paths; and

a switch coupled to the audio decompressors, wherein the audio decompressors provide audio signal associated with video signals, wherein the switch operates to select an audio output from one of the audio decompressors, and wherein at least one of the tuners and at least one of the audio decompressors are located on an upgrade card inserted into an existing set top terminal.

Claim 43 (original): The apparatus of claim 42, further comprising a first decryptor and a first memory in the first signal path and a second decryptor and a second memory in the second signal path.

Claims 44-45 (canceled).

Claim 46 (previously presented): The apparatus of claim 42, further comprising a video combiner, the video combiner combining a processed, scaled and repositioned first signal and a processed second video signal for display, wherein the processed, scaled and repositioned first video signal is overlaid on the processed second video signal.

Serial No. 09/252,485

Page 4 of 14

Claim 47 (original): The apparatus of claim 46, wherein a size of the overlaid first video signal is smaller than a size of the processed second video signal.

Claim 48 (previously presented): The apparatus of claim 42, further comprising a video combiner, the video combiner combining a processed, scaled and repositioned first signal and a processed second video signal for display, wherein the processed second video signal is scaled and repositioned, and wherein the processed, scaled and repositioned first and second video signals are displayed in a split screen format.

Claim 49 (canceled).

Claim 50 (currently amended): The apparatus of claim 42 49, wherein the first and the third video signals are overlaid on the second video signal.

Claim 51 (currently amended): The apparatus of claim 42 49, wherein the first, second and third video signals are displayed in a split screen format.

Claim 52 (canceled).

Claim 53 (previously presented): The apparatus of claim 42, wherein processed, scaled and redirected video signals are provided as digital signals for display on a digital television.

Claim 54 (previously presented): The apparatus of claim 42, wherein the first signal path includes a first NTSC encoder and the second signal path includes a second NTSC encoder, the first and the second NTSC encoders operable to convert processed video signals and processed, scaled, repositioned video signals to analog format for display on an analog television.

Claims 55-56 (canceled).

Serial No. 09/252,485  
Page 5 of 14

Claim 57 (previously presented): The apparatus of claim 42, wherein the first video signal is provided to a first television and the second video signal is provided to a second television.

Claims 58-59 (canceled).

Claim 60 (previously presented): The apparatus of claim 42, wherein the first signal path further includes first audio processing components and the second signal path further includes second audio processing components.

Claim 61 (previously presented): The apparatus of claim 42, further comprising a switch for selecting a first or a second audio signal for output, the switch activated by operation of a remote control.

Claim 62 (original): The apparatus of claim 61, wherein the first and the second audio signals may be provided in multiple languages, and wherein a menu of available languages is present on screen for selection of a desired language.

Claim 63 (original): The apparatus of claim 61, wherein the first and the second audio signals are associated with the first video signal.

Claim 64 (previously presented): The apparatus of claim 61, wherein the switch is operable to select additional audio signals for output, the additional audio signals associated with the second video signal.

Claims 65-73 (canceled).

Claim 74 (previously presented): The apparatus of claim 42, further comprising a microprocessor that controls processing on the first and the second signal paths such

Serial No. 09/252,485

Page 6 of 14

that the first video signal and the second video signal are displayed on one or more displays, and wherein the first signal processing components and the second signal processing components are substantially identical.

Claims 75-76 (canceled).

Claim 77 (currently amended): An apparatus for outputting a plurality of audio signals for at least one video signal, comprising:

a plurality of tuners for tuning to a plurality of programs;

a plurality of video decompressors; and

a plurality of audio decompressors, wherein each of the plurality of audio and video decompressors corresponds to and is connected to the plurality of tuners and wherein the plurality of programs are comprised of both audio and video signals and wherein the at least one video signal may have more than one of the plurality of audio signals corresponding therewith; and

a switch coupled to the audio decompressors, wherein the audio decompressors provide audio signal associated with video signals, and wherein the switch operates to select an audio output from one of the audio decompressors;

wherein at least one of the tuners and at least one of the audio decompressors are located on an upgrade card-inserted into an existing set top terminal.

Claim 78 (currently amended): A set top terminal that outputs multiple video signals, comprising:

first signal processing components, wherein the first signal processing components process a first video signal, the first signal processing components comprising:

a first tuner;

a first demodulator coupled to the first tuner;

a first demultiplexor coupled to the first demodulator;

a first video/graphics/text demultiplexor coupled to the first demultiplexor,

Serial No. 09/252,485

Page 7 of 14

wherein the first video/graphics/text demultiplexor separates graphics, video and text from the first video signal;

a first video decompressor coupled to the first video/graphics/text demultiplexor;

second signal processing components, wherein the second signal processing components process a second video signal, the second signal processing components also operable to scale and redirect the second video signal, the second signal processing components comprising:

a second timer;

a second demodulator coupled to the second tuner;

a second demultiplexor coupled to the second demodulator;

a second video/graphics/text demultiplexor coupled to the second demultiplexor,

wherein the second video/graphics/text demultiplexor separates graphics, video and text from the second video signal; and

a second video decompressor coupled to the second video/graphics/text demultiplexor;

audio decompressors in the first and second signal paths;

a switch coupled to the audio decompressors, wherein the audio decompressors provide audio signal associated with video signals, wherein the switch operates to select an audio output from one of the audio decompressors and wherein at least one of the tuners and at least one of the audio decompressors are located on an upgrade card inserted into an existing set top terminal; and

an upgrade port capable of receiving a hardware upgrade, enabling an electrical connection of the hardware upgrade to the apparatus.

Claim 79 (currently amended): An apparatus that outputs multiple video signals, comprising:

first signal processing components, wherein the first signal processing components process a first video signal, the first signal processing components comprising:

a first tuner;

Serial No. 09/252,485

Page 8 of 14

a first demodulator coupled to the first tuner;  
a first demultiplexor coupled to the first demodulator;  
a first video/graphics/text demultiplexor coupled to the first demultiplexor,  
wherein the first video/graphics/text demultiplexor separates graphics, video and text  
from the first video signal; and

a first video decompressor coupled to the first video/graphics/text demultiplexor;  
and

second signal processing components, wherein the second signal processing  
components process a second video signal, the second signal processing components  
also operable to scale and redirect the second video signal, the second signal  
processing components comprising:

a second tuner;

a second demodulator coupled to the second tuner;

a second demultiplexor coupled to the second demodulator;

a second video/graphics/text demultiplexor coupled to the second demultiplexor,  
wherein the second video/graphics/text demultiplexor separates graphics, video and  
text from the second video signal; and

a second video decompressor coupled to the second video/graphics/text  
demultiplexor, wherein the second signal processing components are located on an  
expansion card inserted into upgrade the apparatus; and

audio decompressors in the first and second signal paths;

a switch coupled to the audio decompressors, wherein the audio decompressors  
provide audio signal associated with video signals, wherein the switch operates to  
select an audio output from one of the audio decompressors and wherein at least one of  
the tuners and at least one of the audio decompressors are located on an upgrade card  
inserted into an existing set top terminal.